FWS Series

Waterstop Fitting

FWS Series Waterstop Fitting provides a flush mount, "pour-in-place" embedded fitting, that allows a direct connection between in-pool components with piping or conduit. Fitting may be floor or wall mounted.

Specification:

FWS Series Waterstop Fitting; consists of a coupling with an integral waterstop plate, bonding lug and female threaded connections. Construction is cast bronze, copper and brass with a natural finish.




Details


TECHNICAL NOTES:

- WATERSTOP FITTING INTENDED FOR FORMED CONCRETE OR GUNITE SHOTCRETE APPLICATIONS.
 THIS PRODUCT IS NOT INTENDED FOR POND/POOL LINER APPLICATIONS.
- 2. WATERSTOP MUST BE BONDED UTILIZING A #8 AWG SOLID COPPER WIRE.


Model Number		Dimensions	
	FNPT	Α	В
FWS-050	1/2"	3½"	1¾"
FWS-075	3/4"	3½"	1¾"
FWS-100	1"	5"	1¾"
FWS-125	1¼"	5"	3"
FWS-150	1½"	5"	3"
FWS-200	2"	5"	3"
FWS-300	3"	7"	5¼"
FWS-400	4"	7"	51⁄4"



FRONT VIEW



PLAN VIEW



ELEVATION VIEW

2021-01

